

DECOSTAR 51S ST 35 W 12 V 36° GU5.3

DECOSTAR 51S STAR | Halogen dichroic reflector lamps with 51 mm diameter and glass panel



- General illumination
- Entrance lighting
- Workplace lighting
- Kitchen lighting
- Mirror lighting
- Object lighting

Product benefits

- Brilliant accent light
- $\boldsymbol{\cdot}$ Dichroic reflector reduces the heat in the light beam by up to 66 %
- · Approved for use in open luminaires (to IEC 60598-1)
- UV filter

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R_a: 100
- Base: GU5.3



Technical data

Electrical data

Rated wattage	35 W
Nominal wattage	35 W
Nominal voltage	12 V
Rated power factor λ	1.00

Light technical data

Luminous intensity	1000 cd
Beam angle	36 °
Color temperature	2900 K
Color rendering index Ra	100
Starting time	0.0 s
Warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80

Dimensions & weight

Overall length	46.0 mm
Diameter	51.0 mm
Outer bulb	MR51

Colors & materials

Lamp mercury content	0.0 mg
Mercury-free	Yes

Lifespan

Nominal lamp life time	3000 h
Rated lamp life time	3000 h
Number of switching cycles	1000000 1)

Product datasheet



Lifespan

 $^{1)}$ At 1 s on / 1 s off

Additional product data

Base (standard designation)	GU5.3
-----------------------------	-------

Capabilities

Dimmable	Yes
Burning position	Any

Country specific categorizations

ILCOS	HRGS//UB-25-12-GU5,3-51/36
Order reference	44865 ST WFL



Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4008321200402	Blister 2	92 mm x 32 mm x 140 mm	73.35 g	0.41 dm ³
4008321200419	Shipping carton box 20	254 mm x 134 mm x 290 mm	1029.92 g	9.87 dm³

Product datasheet



References / Links

For light distribution curves see

www.osram.com

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.